



SKF BEARING MANUFACTURING CO.,LTD.



30 mm x 72 mm x 19 mm KOYO 30306DJR tapered roller bearings

Bearing No. 30306DJR

30306DJR Bearing 2D drawings and 3D CAD models

Size	30x72x20.75 mm
Bore Diameter	30 mm
Outer Diameter	72 mm
Width	20,75 mm
d	30 mm
D	72 mm
T	20,75 mm
B	19 mm
C	14 mm
a	23,7 mm
r min.	1,5 mm
r2 min.	1,5 mm
da min.	38,5 mm
da max	40 mm
Da min	55 mm
Da max.	63,5 mm
Db min.	68 mm
ra max.	1,5 mm
rb max.	1,5 mm
Weight	0,4 Kg
Basic dynamic load rating (C)	50,9 kN
Basic static load rating (C0)	54,9 kN
(Grease) Lubrication Speed	4900 r/min
(Oil) Lubrication Speed	6800 r/min
Calculation factor (e)	0,83



SKF BEARING MANUFACTURING CO.,LTD.

Calculation factor (Y0)	0,4
Category	Tapered Roller Bearing Assemblies
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.4
EAN	0605790247057
Product Group	B04334
Precision Class	Standard
Component	Assembly
Basic Number	30306
Number of Tapered Rows	Single Row
Inch - Metric	Metric
Other Features	High Load Capacity Steep Contact Angle
Long Description	Assembly; Standard Precision; 30MM Bore; 72MM Outside Diameter; 20.75MM Assembly Width; Single Row of Rollers
Category	Tapered Roller Bearings Assembly
UNSPSC	31171516
Harmonized Tariff Code	8482.20.00.00
Noun	Bearing
Keyword String	Tapered
Manufacturer URL	http://www.koyousa.com
Manufacturer Item Number	30306DJR
Weight / LBS	0.882
Bore	1.181 Inch 30 Millimeter
Flange Outside Diameter	0 Inch 0 Millimeter
Outside Diameter	2.835 Inch 72 Millimeter
Assembly Width	0.817 Inch 20.75 Millimeter



SKF BEARING MANUFACTURING CO.,LTD.

Bearing No.	30306DJR
r(min)	1.5
r1(min)	1.5
Cr	63.5
C0r	54.9
Cu	7.70
Grease lub.	4900
Oil lub.	6800
a	23.7 mm
da(min)	38.5
db(max)	40
Da(max)	63.5
Da(min)	55
Db(min)	68
Sa(min)	3
Sb(min)	6.5
ra(max)	1.5
rb(max)	1.5
e	0.83
Y1	0.73
Y0	0.40
(Refer.)Mass(kg)	0.400