



SKF BEARING MANUFACTURING CO.,LTD.

30 mm x 72 mm x 19 mm ZVL 31306A tapered roller bearings



Bearing No. 31306A

31306A Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|----------------|
| Size | 30x72x20.75 mm |
| Bore Diameter | 30 mm |
| Outer Diameter | 72 mm |
| Width | 20,75 mm |
| d | 30 mm |
| D | 72 mm |
| T | 20,75 mm |
| B | 19 mm |
| C | 14 mm |
| a | 23 mm |
| r1 min. | 1,5 mm |
| r2 min. | 1,5 mm |
| da max | 39 mm |
| Da min | 55 mm |
| Da max. | 65 mm |
| db min | 37 mm |
| Db min. | 68 mm |
| ra max. | 1 mm |
| Weight | 0,395 Kg |
| Basic dynamic load rating (C) | 46,4 kN |
| Basic static load rating (C0) | 50,1 kN |
| (Grease) Lubrication Speed | 5 300 r/min |
| (Oil) Lubrication Speed | 7 100 r/min |
| Calculation factor (e) | 0,83 |
| Calculation factor (Y) | 0,7 |



SKF BEARING MANUFACTURING CO.,LTD.